

06-05-00

A

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application

PATENT APPLICATION

Inventor: Michael Heideman

Art Unit: Unknown

SC/Serial No.: Unknown

Examiner: Unassigned

Filed: Herewith

Customer No.: 23910

Title: A METHOD, SYSTEM AND ARTICLE OF  
MANUFACTURE FOR MINIMIZING TRAVEL  
TIME TO A USER SELECTED LOCATION

**CERTIFICATE OF MAILING BY "EXPRESS MAIL"  
UNDER 37 C.F.R. §1.10**

"Express Mail" mailing label number: EL 498 237 319 US  
Date of Mailing: June 1, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service, utilizing the "Express Mail Post Office to Addressee" service addressed to Box **PATENT APPLICATION**, Commissioner for Patents, Washington, DC 20231 and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.

Alice D. Kisch  
Alice D. Kisch

(Signature)

Signature Date: June 1, 2000**UTILITY PATENT APPLICATION TRANSMITTAL LETTER UNDER 37 C.F.R. §1.53(b)**

Box **PATENT APPLICATION**  
Commissioner for Patents  
Washington, DC 20231

Sir:

Transmitted herewith for filing is the patent application identified as follows:

Inventor: Michael Heideman

Title: A METHOD, SYSTEM AND ARTICLE OF MANUFACTURE FOR  
MINIMIZING TRAVEL TIME TO A USER SELECTED LOCATION

No. of pages in Specification: 18; No. of Claims: 16.  
(plus title cover page)

No. of Sheets of Drawings: 7; Formal:   , Informal:   ✓  .



The filing fee pursuant to 37 C.F.R. §1.16 is determined as follows:

No. Filed	No. Extra	Rate Small Entity/ Other Than Small Entity		
Basic Fee		\$345.00 \$690.00	=	\$690.00
Total Claims <u>16</u> - 20 = <u>0</u>	X	\$ 9.00 \$ 18.00	=	\$0
Independent Claims <u>4</u> - 3 = <u>1</u>	X	\$ 39.00 \$ 78.00	=	\$78.00
First Presentation of Multiple Dependent Claim(s) <u>0</u>		\$130.00 \$260.00	=	\$0
		Total	=	\$768.00

☒ A check in the amount of \$768.00 to cover the filing fee (\$768.00) is enclosed.

☒ The Commissioner is hereby authorized to charge underpayment of any additional fees or credit any overpayment associated with this communication to Deposit Account No. 06-1325. A duplicate copy of this authorization is enclosed.

This application is filed pursuant to 37 C.F.R. §1.53(b) in the name of the above-identified Inventor.

Please direct all correspondence concerning the above-identified application to the following address:

Martin C. Fliesler, Esq.  
FLIESLER DUBB MEYER & LOVEJOY LLP  
Four Embarcadero Center, Suite 400  
San Francisco, California 94111-4156  
Telephone: (415) 362-3800

Respectfully submitted,

Date: 6/1/00

By: Kirk J. DeMiro

Kirk J. DeMiro  
Reg. No. 35,854

FLIESLER DUBB MEYER & LOVEJOY LLP  
Four Embarcadero Center, Suite 400  
San Francisco, California 94111-4156  
Telephone: (415) 362-3800

**A METHOD, SYSTEM, AND ARTICLE OF MANUFACTURE FOR  
MINIMIZING TRAVEL TIME TO A USER SELECTED LOCATION**


**Inventor**

**Michael Heideman**

**CERTIFICATE OF MAILING BY "EXPRESS MAIL"  
UNDER 37 C.F.R. § 1.10**

"Express Mail" mailing label number: EL 498 237 319 US  
Date of Mailing: June 1, 2000

I hereby certify that this correspondence is being deposited with the United States Postal Service, utilizing the "Express Mail Post Office to Addressee" service addressed to Box Patent Application, Commissioner for Patents, Washington, D.C. 20231 and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.

  
\_\_\_\_\_  
Alice D. Kisch (Signature)  
Signature Date: June 1, 2000

**A METHOD, SYSTEM, AND ARTICLE OF MANUFACTURE FOR  
MINIMIZING TRAVEL TIME TO A USER SELECTED LOCATION**

**Inventor**

**Michael Heideman**

**5    Field of the Invention**

The present invention relates to information systems, and in particular, obtaining a user selected type of location having a minimum travel time.

**Background of the Invention**

- 10        Often individuals would like to obtain information regarding local businesses or points of interest. For example, a salesman in the field may be interested in knowing the five closest restaurants from a customer site. The salesman may not be familiar with the area surrounding the customer site.
- 15        The salesman would like to reduce his travel time to a particular restaurant in order to keep other appointments. A map or address in a directory may provide the salesman with the closest physical location of a restaurant, but the closest physical restaurant may not be the restaurant having the minimum travel time from the customer site.
- 20        Also, a map or directory may not be readily accessible or may be outdated. The closest physical restaurant may be on the other side of a river, railroad tracks, or other obstacles. Similarly, the closest physical restaurant may require the use of a particularly congested highway which would increase travel time.

Furthermore, there may be a few restaurants having similar travel times. The salesman may have a preference of one of the restaurants over the other, if they all have similar travel times.

Therefore, it is desirable to provide a system, method, and article  
5 of manufacture for providing individuals with user selected types of  
locations having minimal travel times. The system, method, and article  
of manufacture should provide a plurality of locations within a user  
selected category having the shortest travel time from a particular site  
or origin. The plurality of locations should be updated and quickly  
10 accessible which enables the individual to save valuable time and  
energy while providing informed selections.

### **SUMMARY OF THE INVENTION**

A method for obtaining a minimum travel time to a predetermined  
destination is provided. A user requests a search category. A plurality  
15 of locations in the search category are obtained within a selected area.  
A first travel time is computed from a first location to a second location  
in the plurality of locations. The first travel time and respective first  
location is stored and provided to the user.

According to an embodiment of the present invention, a second  
20 travel time is computed from the first location to a third location in the  
plurality of locations. The first travel time and second travel time are  
then sorted by ascending order and provided to the user.

According to another embodiment of the present invention, the  
obtaining step includes searching a database for a plurality of locations  
25 within a selected geographical area.

According to another embodiment of the present invention, a method for obtaining a minimum travel time to a plurality of locations in a user selected category is provided. A user requests a search category such as restaurants or dry cleaners. A plurality of locations in the search category within a selected area surrounding the user are selected. A determination is made whether the selected area should be expanded based upon the plurality of locations. A first travel time is estimated by dividing the distance from the first location to the second location by a maximum speed. A determination is made whether the estimated first travel time is less than a predetermined limit. A first travel time is computed from a first location to a second location in the plurality of locations. The first travel time and respective first location is stored. A second travel time is computed from a first location to a third location in the plurality of locations. The first travel time is sorted with the second travel time based upon ascending values.

According to an embodiment of the present invention, a system for obtaining a minimum travel time from an origin to a first location is provided. The system comprises a communication device for inputting a user selected category and receiving a first location, from the user selected category, having the minimum travel time. A transmitter/-receiver is coupled to the communication device and receives the user selected category and transmits the first location. A processing device is coupled to the transmitter/receiver and computes the minimum travel time.

According to yet another embodiment of the present invention, an article of manufacture having a computer readable medium for providing a minimum travel time from an origin to a first location in a user selected category is provided. The article of manufacture

comprises a first software program for obtaining a user selected category. A second software program obtains a plurality of locations in the user selected category within a predetermined area surrounding the location of the user. A third software program computes the travel  
 5 time from the user location to the respective plurality of locations. A fourth software program sorts the plurality of locations based on the respective travel times. A fifth software program provides the sorted plurality of locations and respective travel times to the user.

Other aspects and advantages of the present invention can be  
 10 seen upon review of the figures, the detailed description, and the claims which follow. In the figures, like reference numerals indicate like components.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 illustrates a system for minimizing travel time to a user  
 15 selected type of location, according to an embodiment of the present invention;

Figs. 2-4 illustrate a map, according to an embodiment of the present invention;

Figs. 5a-b is a flow chart illustrating a travel time minimizing  
 20 software program 41 shown in Fig. 1, according to an embodiment of the present invention; and,

Fig. 6 is a sorted list of locations in a user selected category ordered by respective ascending travel times from an origin.

**DETAILED DESCRIPTION**

Fig. 1 illustrates a travel time minimizing system 10 for determining a type of location having the shortest travel time from an origin, according to an embodiment of the present invention. System 10 includes communication device 21. In an embodiment, communication device 21 is a wireless device such as a cellular telephone. In alternate embodiments, communications device 21 may be a personal digital assistant, computer, or equivalent thereof.

In an alternate embodiment, communication device 21 may be wired. For example, communication device 21 is a pay telephone in an alternate embodiment.

A user 20 operates communication device 21 in order to obtain desirable types of locations having the shortest travel time from where user 20 is currently positioned. In an alternate embodiment, a user obtains desirable locations having the shortest travel time from a specified origin which is not necessarily where user 20 is currently positioned.

Communication transmitter/receiver 30 is used to obtain and transmit information to communication device 21. In an embodiment, communication transmitter/receiver 30 is a cellular transmitter/receiver for communicating with a cellular telephone.

Processing device 40 is wired to communication transmitter/receiver 30 in an embodiment of the present invention. In alternate embodiments, processing device 40 is connected to transmitter/receiver 30 by a wireless connection. In an embodiment, processing device 40 is a computer such as a computer server. In alternate embodiments, processing device 40 is a distributed collection of processing devices.



In an embodiment, processing device 40 stores travel time minimizing software 41 in processing device memory.

In an alternate embodiment, travel time minimizing software may be stored on a computer readable medium, including but not limited to, a hard disk, a floppy disk, an optical disk or equivalent thereof. In an embodiment, travel time minimizing software is written in the C, C + + , or Java™ computer languages, singly or in combination therewith.

Figs. 5a-b illustrate the operation of an embodiment of travel time minimizing software 41.

Fig. 6 illustrates an output of travel time minimizing software 41 to communication device 21 in response to a user 20 input.

Processing device 40 is connected to persistence storage 42 which stores maps and other information accessed by software 41. In an embodiment, persistence storage 42 is a large capacity disc drive for storing maps, business locations, and other information accessed by software 41. In alternate embodiments, persistence storage 42 includes multiple storage devices.

Figs. 2-4 are maps of a typical urban city. For example, Fig. 2 illustrates freeways, railroads, parks and local roads. User 20 may be at location 100 and interested in knowing where the closest restaurant is located from his current location 100 or origin. In alternate embodiments, user 20 may be interested in the closest dry cleaner, grocery store, retail store, theater, gas station, customer site, tourist site, or any other point of interest. For example, user 20 is interested in knowing the closest restaurant by travel time.

Fig. 3 illustrates how an individual can select a restaurant based on determining the closest physical restaurant from location 100. Fig. 3 illustrates circles 110, 111, 112, and 113 which have radiuses of 300

meters, 600 m, 1.2 km, and 1.8 km from location 100. User 20 then  
 may look on a directory or a map for the closest restaurant falling within  
 the smallest circle. For example, restaurant 150 falls within circle 111  
 and is approximately 0.38 km away "as the crow flies", or has the  
 5 closest physical location from location 100. However, as one may  
 observe it may take user 20 a large amount of time to get to restaurant  
 150. There are two railroad tracks between location 100 and restaurant  
 150 and user 20 is required to use crossings which may be congested.  
 User 20 could miss important appointments attempting to go to a  
 10 restaurant which may have been the closest "as the crow flies", but  
 may take a large amount of travel time.

Fig. 4 illustrates zones or areas having businesses or points of  
 interest having minimum travel time from location 100. As can be  
 observed, these zones are not simple circles based on a physical  
 distance between an origin and possible destination. These zones 161,  
 15 162, and 163 are determined based on potential pathways or roads user  
 20 may take to get to a potential destination. The zones are also  
 determined by, but not limited to, the speed limit of a potential  
 pathway, number of turns, and potential traffic congestion. For  
 example, zone 162 has peaks 166 and 167 because user 20 can easily  
 access El Camino Real which has a relatively high speed limit and few  
 turns. In an embodiment of the present invention, the zones may be  
 altered based on traffic congestion and time of day. Using the present  
 method, system, or software, user 20 is able to determine that  
 25 restaurant 160, which is about 0.71 km away, is actually the restaurant  
 with the minimum travel time as opposed to restaurant 150 which has  
 the closest physical location, but a greater travel time.

Figs. 5a-b is a flow chart of travel time minimizing software 41 shown in Fig. 1. As one of ordinary skill in the art would appreciate, Figs. 5a-b show logic blocks for performing specific functions. In alternate embodiments, more or less logic blocks may be used. Similarly, logic blocks may represent software programs, software objects, software subroutines, software code fragments, hardware operations, user operations, singly or in combination.

Travel time minimizing method 500 initiates by inputting or reading a plurality of default values as illustrated by logic block 400 and 401. A default search area shape and size is input in logic block 400. For example, the default search area shape and size may be a bounding box in latitude/longitude of 0.001° on a side. The origin is then entered as illustrated by logic block 401. In an embodiment, the origin may be a user's current location. In an alternate embodiment, the origin may be another location, such as a location at which the user plans to be in the near future. A selection category or criterion is then also entered, as illustrated by logic block 401. In an embodiment, the user category is obtained from a user selecting a category displayed on a cellular telephone display. For example, the user may select the restaurant category displayed on the cellular telephone. A desired result count is then specified by the portal of the users carrier, as illustrated in logic block 401. The desired result count is the number of candidate locations in the selected category to be returned to the user.

Logic block 402 illustrates defining a particular search area or zone. For example, area 161 illustrated in Fig. 4 may be a first zone. In an alternate embodiment, the first zone may be specified by a rectangle. As will be described below, if not enough candidate

locations are found in the first zone, the first zone will be expanded into a larger second zone.

A search of database 43 for locations in the selected category and in the defined zone is then performed, as illustrated by logic block  
5 403.

A determination is then made in logic block 404 whether the candidate locations returned by the search of database 43 in logic block 403 meet a threshold number of candidates or minimum proximity candidate count. In an embodiment, a minimum proximity candidate  
10 count is 29.

If the minimum proximity candidate count is met, control passes to logic block 405. Otherwise, control passes to logic block 416.

In logic block 416, a determination is made whether an expansion of the search zone will exceed a predetermined limit. For example, a  
15 predetermined limit may be the city limits. In an alternate embodiment, the predetermined limit may be user defined. If an expansion of the search zone does not exceed the maximum limit, control passes to logic block 415. In an alternate embodiment, the predetermined limit may be category dependent.

20 In logic block 415, a search zone is expanded. For example, search zone 161 may be expanded to search zone 162, as illustrated in Fig. 4. In an alternate embodiment, the expanded search zone may be characterized by a rectangle.

25 After expansion of the search area in logic block 415, control passes to logic block 402 and logic steps may be repeated.

If the expansion of the search area will exceed the maximum limit, a determination is made in logic block 417 whether there are any proximity candidates. If there are proximity candidates, control

transitions to logic block 405. Otherwise, the user is notified that no candidate locations are available, as illustrated in logic block 418, and the method 500 exits.

If any proximity candidate exists or the minimum proximity  
5 candidate count is met, control transitions to logic block 405.

In logic block 405, the distance from the origin to each proximity candidate is computed. The proximity candidates and their respective distances are sorted by ascending distances.

A candidate index N is then set to 1 as illustrated in logic block  
10 406 in Fig. 6.

In logic block 407, the shortest traveling time between the origin and the Nth proximity candidate is estimated as known by one of ordinary skill in the art.

In logic block 408, the proximity candidate and respective  
15 estimated traveling time is added to the destination list in ascending order according to travel time.

A determination is then made in logic block 409 whether there are more than N proximity candidates. If there are not more than N proximity candidates, control transitions to logic block 419 where a  
20 determination is made whether a search expansion will exceed the maximum limit. If the maximum limit is not exceeded, control transitions to logic block 415 and the logic blocks are repeated. Otherwise, control transitions to logic block 420 and the user is notified that some locations are found but may not have minimal estimated  
25 traveling time due to the search areas default maximum size limit specified in logic block 450.

If there are more than N proximity candidates, control passes to logic block 410.

A determination is made in logic block 410 whether N is less than the desired result count. If N is less than the desired result count, control passes to logic block 414 where N is incremented. Control then transitions to logic block 407 where the logic blocks may be repeated.

- 5 If N is not less than the desired result count, control passes to logic block 411.

- 10 An estimated lower bound traveling time is estimated in logic block 411. The estimated lower bound traveling time is estimated by dividing the proximity distance from the origin to the  $N + 1$  candidate by the maximum speed. If the search area is not circular, then it is also necessary to determine whether the search area fully contains a circle of radius equal to the distance to the candidate. This estimation is done in order to prevent unnecessary computation of a traveling time which would not provide a proximity candidate with a shorter traveling time than already calculated. This allows for enhanced speed in providing information to users.
- 15

- 20 A determination in logic block 412 is made whether the driving time to the selected result count candidate in ascending order by traveling time is less than the calculated lower bound traveling time. If the traveling time to the selected result count candidate in ascending order is less than the lower bound, control passes to logic block 413 where the destination list of proximity candidates from a user selected category is output to the user. In an embodiment, the list may be displayed or provided by an audio list. Method 500 then exits.

- 25 If the traveling time to N is not less than the computed lower bound, control passes to logic block 414 where N is incremented. Control then transitions to logic block 407 where the steps are repeated.

Fig. 6 illustrates a list of locations from a user selected category having minimal traveling time from an origin. The list of locations is provided in ascending travel time order and is provided by travel time minimizing software 41.

5        Column 500 lists candidate restaurants near an origin, such as location 100 in Figure 2. Column 501 lists the addresses of respective restaurants in column 500. Column 502 lists in ascending order the calculated travel time to the respective restaurants in column 500.

10        For example, "Harry's Hofbrau" takes approximately 1.38 minutes travel time from location 100, while the "Denny's Restaurant" takes 2.27 minutes travel time.

15        Column 503 lists distances to the respective restaurants in column 500 using the roads as illustrated in Figure 2. Column 504 lists the proximity distance or "as the crow flies" distance to the respective restaurants.

20        Finally, column 505 lists the proximity order of the respective restaurants or the ranking of the restaurants based on the proximity distance to the restaurant from location 100. Note that certain restaurants may have a very low proximity rank, yet a very high travel time. The 11<sup>th</sup> closest restaurant by proximity ("Pampas Restaurant") turns out to be the 3<sup>rd</sup> closest by travel time. Conversely, the 1<sup>st</sup> closest restaurant by proximity "Wanns Party Givers, Inc." is the 11<sup>th</sup> closest by travel time.

25        The foregoing description of the preferred embodiments of the present invention has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in the art. The

embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, thereby enabling others skilled in the art to understand the invention for various embodiments and with the various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the following claims and their equivalents.



## CLAIMS

The claimed invention is:

- 1           1.     A method for obtaining a travel time, comprising the steps  
2     of:  
3           (a)     requesting a search category from a user;  
4           (b)     obtaining a plurality of locations in the search category  
5     which are within a selected area;  
6           (c)     computing a first travel time from a first location to a  
7     second location in the plurality of locations; and,  
8           (d)     storing the first travel time and respective first location.
- 1           2.     The method of claim 1, further comprising the steps of:  
2           computing a second travel time from the first location to a third  
3     location in the plurality of locations; and,  
4           sorting the first travel time and second travel time by ascending  
5     order.
- 1           3.     The method of claim 1, wherein the search category is  
2     restaurants and the first location is a first restaurant.
- 1           4.     The method of claim 1, wherein the search category is gas  
2     stations and the first location is a gas station.
- 1           5.     The method of claim 1, further comprising the step of  
2     expanding the selected area.

1           6.     The method of claim 1, further comprising the step of:  
2           determining whether a preselected number of locations have  
3           respective travel times computed.

1           7.     The method of claim 1, further comprising the steps of:  
2           estimating the first travel time by dividing a distance from the first  
3           location to the second location by a maximum speed; and,  
4           determining whether the estimated first time is less than a  
5           predetermined limit.

1           8.     The method of claim 1, wherein the obtaining step includes  
2           searching a database for a plurality of locations within a selected  
3           geographical area.

1           9.     The method of claim 1, wherein the requesting step further  
2           includes prompting a user on a cellular phone display.

1           10.    A method for obtaining a travel time, comprising the steps  
2           of:

- 3           (a)     requesting a search category from a user;  
4           (b)     obtaining a plurality of locations in the search category  
5           which are within a selected area;  
6           (c)     determining whether the selected area should be expanded  
7           based upon the plurality of locations;  
8           (d)     estimating a first travel time by dividing the distance from  
9           the first location to the second location by a maximum speed;  
10          (e)     determining whether the estimated first travel time is less  
11          than a predetermined limit;

- 12 (f) computing a first travel time from a first location to a
- 13 second location in the plurality of locations;
- 14 (g) storing the first travel time and respective first location;
- 15 (h) computing a second travel time from a first location to a
- 16 third location in the plurality of locations; and,
- 17 (i) sorting the first travel time with the second travel time
- 18 based upon ascending values.

1 11. A system for obtaining a minimum travel time from an  
2 origin to a first location, comprising:

3 (a) a communication device for inputting a user selected  
4 category and receiving a first location, from the user selected category,  
5 having the minimum travel time;

6 (b) a transmitter/receiver, coupled to the communication  
7 device, for receiving the user selected category and transmitting the  
8 first location; and,

9 (c) a processing device, coupled to the transmitter/receiver, for  
10 computing the minimum travel time.

1 12. The system of claim 11, wherein the communication device  
2 is a cellular telephone.

1 13. The system of claim 11, wherein the category is a  
2 restaurant category.

1 14. The system of claim 11, wherein the processing device is  
2 a computer.

1           15. The system of claim 11, further comprising:  
2           (d) a persistence storage device, coupled to the processing  
3 device, for storing map information.

1           16. An article of manufacture having a computer readable  
2 medium, comprising:

- 3           (a) a first software program for obtaining a user selected  
4 category;  
5           (b) a second software program for obtaining a plurality of  
6 locations in the user selected category within a  
7 predetermined area surrounding the location of the user;  
8           (c) a third software program for computing the travel time  
9 from the user location to the respective plurality of  
10 locations;  
11           (d) a fourth software program for sorting the plurality of  
12 locations based on the respective travel times; and,  
13           (e) a fifth software program for providing the sorted plurality  
14 of locations and respective travel times to the user.

**ABSTRACT**

A method, system, and article of manufacture for providing a plurality of locations having minimal travel time from a user's location is provided. A user enters a search category into a wireless communication device. The user is then provided with a list of locations having minimal traveling time from the present user's location. Search categories may include, for example, restaurants, theaters, grocery stores, or dry cleaning.

10




FIG. 1

LOCATION 100



001030 50055500

LOCATION 100

RESTAURANT 150





FIGURE 3



LOCATION 100



## RESTAURANT 160

FIGURE 4

# TRAVEL TIME MINIMIZING METHOD 500





FIG. 5a

# TRAVEL TIME MINIMIZING METHOD 500



Restaurant	Address	DriveZone		DriveZone		Proximity in Km	Proximity in Km	Proximity Ordering
		Time in Minutes	Distance in Km	Time in Minutes	Distance in Km			
FABROS RESTAURANT	2915 EL CAMINO REAL	1.37	0.88		0.71			4
HARRY'S HOFBRAU	1909 EL CAMINO REAL	1.38	1.21		0.84			7
PAMPAS RESTAURANT	1836 EL CAMINO REAL	1.47	1.32		0.93			11
THAI HOUSE RESTAURANT	1742 EL CAMINO REAL	1.57	1.43		1.05			12
EL GUANACO MEXICAN	2950 MIDDLEFIELD RD	1.62	0.82		0.56			2
LA PACHANGA RESTAURANT	3102 MIDDLEFIELD RD	1.77	0.95		0.77			6
EL NOPAL RESTAURANT	175 5TH AVE	1.83	0.95		0.92			9
LA ESTRELLITA	2205 MIDDLEFIELD RD	1.98	1.70		0.64			3
IXTAPA GRILL	3143 MIDDLEFIELD RD	1.98	1.14		0.87			8
LA FORTUNA RESTAURANT	3180 MIDDLEFIELD RD	2.03	1.21		0.93			10
WANNAS PARTY GIVERS INC	2884 MIDDLEFIELD RD	2.07	1.00		0.38			1
EJS STEAK & SEAFOOD	135 BUCKEYE ST	2.08	1.37		0.74			5
UNA MAS RESTAURANTS INC	1023 EL CAMINO REAL	2.25	2.25		1.85			30
DENNY'S RESTAURANT	1201 BROADWAY ST	2.27	2.19		1.32			17
HIDEWAY	739 CHESTNUT ST	2.32	1.98		1.11			14

Figure 6

m:\kjd\canvas\airf\1013\fig\_6.xls